

2013-2016 ENDURO 26, 29, 650b, SX



BEARING KIT PART # 98914-5000				SPECIFICATION				
ITEM #	LOCATION	PART	QTY	 MATERIAL	DESCRIPTION	Ø OD	Ø ID	 WIDTH
1-A	Bottom Bracket	Bearing	2	Steel	1524F	24	15	5
1-B		Spacer (Enduro 26, 29, SX)	2	Aluminum	Square profile	21.6	15.1	3
1-C		Spacer (Enduro 29, SX)	1	Aluminum	Square profile (replaces 1.c when using ft. der)	21.6	15.1	3.9
1-C		Spacer (Enduro 650b)	1	Aluminum	Tapered profile	29	15.1	9.7
1-D		Sleeve (Enduro 26)	1	Aluminum	With o-rings x 2	19	15	38
1-E		Sleeve (Enduro 29, SX)	1	Aluminum	With o-rings x 2	19	15	44
1-F		O-ring	2	Rubber		19.6	14.8	2.4
1-G	Dropout	Bearing	4	Steel	6801V-2RS	21	12	5
1-H		Spacer (outer)	4	Aluminum	With dust shield. Chamfer faces bearing	20	12.1	2.5
1-I		Spacer (inner)	2	Aluminum	Square profile	18.5	12.1	2
1-J	S-Link @ Seat Tube	Bearing	2	Steel	1524F	24	15	5
1-K		Spacer	2	Aluminum	Square profile	21.6	15.1	3
1-L	S-Link @ Seatstay	Bearing	2	Steel	1524F	24	15	5
1-M		Spacer	2	Aluminum	Square profile	21.6	15.1	3
1-N	S-Link @ Yoke	Bearing	2	Steel	1524F	24	15	5

SPECIALIZED BICYCLE COMPONENTS
 15130 Concord Circle, Morgan Hill, CA 95037
 (408) 779-6229
 0000037545_SC_R3, 06/16
 Please note all instructions are subject to change and updates without notice.
 Please visit www.specialized.com for periodic tech updates.
 Feedback: techdocs@specialized.com

NOTE: Apply blue threadlocker to all threads

BOLT KIT PART # 98914-5001				SPECIFICATION								
ITEM #	LOCATION	PART	QTY	 MATERIAL	Ø OD	Ø ID	 WIDTH	 WIDTH	MM	 TOOL	 MM	 TORQUE in-lbf (Nm)
2-A	Bottom Bracket	Axle (Enduro 26)	1	Aluminum				M15	67.5	Allen key	8	215 (24.2)
2-B		Axle (Enduro 29, 650b, SX)	1	Aluminum				M15	79.5	Allen key	8	215 (24.2)
2-C		Axle Washer (Enduro 29, 650b, SX)	1	Aluminum	21	15.2	0.5					
2-D	Dropout	Bolt	2	Aluminum				M12	29	Allen key	6	150 (17)
2-E		Washer	2	Steel	20.5	12.1	0.3					
2-F	S-Link @ Seat Tube	Bolt	2	Aluminum				M15	18	Allen key	8	190 (21.5)
2-G	S-Link @ Seatstay	Bolt	2	Aluminum				M15	18	Allen key	8	190 (21.5)
2-H	S-Link @ Yoke	Bolt	2	Aluminum				M15	16	Allen key	8	190 (21.5)
2-I	Upper shock eye	Bolt	1	Steel				M8	55	Allen key	6	170 (19.2)
2-J		Washer	1	Steel	12.5	8.4	0.3					
2-K	Lower shock eye	Bolt (not included)	0	Aluminum				M8	14	Allen key	5	130 (14.7)